

Technical Data Sheet: Premium Plus

Technical properties

Description

Composition	70% PVC + 30% Fiberglass
Weight	530 g/m ² (±5%) 15.63 oz/yd ² (±5%)
Thickness	0.29 mm (±5%) 0.011 in (±5%)
Roll Width*	1.83 m, 2.44 m, & 3.0 m 72 in, 96 in, & 118 in
Roll Length	25 m, 25 m, & 18.3 m 27.34 yd, 27.34 yd, & 19.68 yd
Light Fastness	Class 4.5 (After 80 AFU)
Opacity	100% Blackout
Flame Retardant	NFPA 701

*Each width has its own price level and item code

Performance evaluations conducted by independent laboratories.

Cleaning and maintenance

<input type="checkbox"/>	<input checked="" type="checkbox"/> Wipe	<input checked="" type="checkbox"/> Vacuum	<input checked="" type="checkbox"/> No wring	<input type="checkbox"/>	<input type="checkbox"/>
--------------------------	--	--	--	--------------------------	--------------------------

1. Hand wash with lukewarm water and mild 5% detergent solution.
2. Wipe gently with a wet sponge.
3. Vacuum clean for regular maintenance.
4. Do not wring dry.
5. Do not bleach.
6. Do not dry clean nor use steam cleaning.

Optical properties

UV Blockage 100 %

Certificates

VERTILUX

IDEAS FOR YOUR SPACE

