

Technical Data Sheet: VX Screen 2900-5%

Technical properties

Description	Standards	
Composition	-	30% PES + 70% PVC
Weight	UNE EN 12127	395 g/m ² (±5%) 11.65 oz/yd ² (±5%)
Thickness	UNE EN ISO 5084	0.57 mm (±5%) 0.022 in (±5%)
Roll Width	-	250 cm, 300 cm 98 in, 118 in
Roll Length	-	30 m 32.8 yds
Openness Factor	Int. Method	Approx. 5%
UV Blockage	Int. Method	Approx. 95%
Mesh/in	UNE EN ISO 13934-1:1999	Warp: 0.32mm Fill: 0.42mm
Color Fastness	AATCC 16-2003	Class 4.5
Flame Retardant	NFPA 701	Pass
Environmental & Health Properties	OEKO Tex® - 100	Certified

Cleaning and maintenance

Wipe	Vacuum		No wring		
------	--------	--	----------	--	--

1. Wipe gently with a wet sponge.
2. Vacuum clean for regular maintenance.
3. Do not wash
4. Do not wring dry.
5. Do not bleach.
6. Do not dry clean nor use steam cleaning.

Optical properties

Chesnut	-	-	-	-
Ebony	10	05	85	12
Ebony Pearl	11	07	82	15
White	19	66	15	24
White Linen	16	59	25	18
White Pearl	10	47	43	17

Certificates

