

## Technical Data Sheet: VX Screen 3000-1%

### Technical properties

Description	Standards	
Composition	-	30% PES + 70% PVC
Weight	UNE EN 12127	480 g/m <sup>2</sup> (±5%)   14.16 oz/yd <sup>2</sup> (±5%)
Thickness	UNE EN ISO 5084	0.62 mm (±5%)   0.024 in (±5%)
Roll Width	-	250 cm, 300 cm   98 in, 118 in
Roll Length	-	30 m   32.8 yds
Openness Factor	Int. Method	Approx. 1%
UV Blockage	Int. Method	Approx. 99%
Mesh/in	UNE EN ISO 13934-1:1999	Warp: 62   Fill: 40
Color Fastness	AATCC 16-2003	Class 4.5
Flame Retardant	NFPA 701	Pass
Environmental & Health Properties	OEKO Tex® - 100	Certified

### Cleaning and maintenance

Wipe	Vacuum		No wring		
------	--------	--	----------	--	--

1. Wipe gently with a wet sponge.
2. Vacuum clean for regular maintenance.
3. Do not wash
4. Do not wring dry.
5. Do not bleach.
6. Do not dry clean nor use steam cleaning.

### Optical properties

White	19	66	15	15
White Linen	16	59	25	12
White Pearl	10	47	43	08
Linen	16	45	39	17
Ebony	04	03	93	02
Ebony Pearl	02	10	88	02
Brown Chocolate	02	07	91	02
Chesnut	06	04	90	04
Taupe	09	42	49	05

## Certificates

